

CHG4001

Cradle for OPI4002



+ Specifications

Power

- Voltage requirement: 6V \pm 5%
- Battery charging time: Ca. 3 hours (full charge)

Durability

- Temperature in operation: 0 to 40 °C / 32 to 104 °F

Physical

- Dimensions (w x h x d):
77 x 51 x 109 mm / 3.03 x 2.01 x 4.29 in
- Weight body: Ca. 80 g / 2.8 oz
- Case: ABS, White

Regulatory & Safety

- Product compliance: CE, RoHS

Sold separately

- Converter cable
- Power supply 100-240V/0.5A, 50/60 Hz, 6V/2A

Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp
- **France:** Issy Les Moulineaux
- **Germany:** Dietzenbach
- **Italy:** Castel Maggiore (BO)
- **Spain:** Valencia
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Renton, WA
- **Japan:** Warabi City

- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** Kariang
- **Brazil:** São Paulo

Opticon, Inc.
2220 Lind Avenue SW
Suite 100
Renton, WA 98057
Toll Free: (800) 636-0090
Local: (425) 651-2120
Fax: (425) 454-0865
Email: sales@opticonusa.com

OPTICON USA

WWW.OPTICONUSA.COM