

IRU2700 Cradle for PHL2700



+ Specifications

Communication

- RS232: Baudrate 1200 bps - 115.2 kbps, half duplex RS232, D Sub 9P F connector
- RS485: Half duplex RS485, 6 pins modular plug connector

Power

- Voltage requirement: 5V
- Battery charging time: Ca. 8 hours

Durability

- Temperature in operation: 0 to 40 °C / 32 to 104 °F
- Temperature in storage: -20 to 60 °C / -4 to 140 °F
- Humidity in operation: 30 - 85% (non-condensing)
- Humidity in storage: 30 - 90% (non-condensing)

Physical

- Dimensions (w x h x d): 90 x 81 x 150 mm / 3.54 x 3.19 x 5.91 in
- Weight body: Ca. 250 g / 8.8 oz
- Case: ABS, Grey

Regulatory & Safety

- Product compliance: EN 55022, EN 55024

Sold separately

- RS232 cable
- RS485 cable
- Power supply 230V/4.5A, 50 Hz, 9V/0.5A

Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp
- **France:** Issy Les Moulineaux
- **Germany:** Dietzenbach
- **Italy:** Castel Maggiore (BO)
- **Spain:** Valencia
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Renton, WA
- **Japan:** Warabi City

- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** Kariong
- **Brazil:** São Paulo

Opticon, Inc.
2220 Lind Avenue SW
Suite 100
Renton, WA 98057
Toll Free: (800) 636-0090
Local: (425) 651-2120
Fax: (425) 454-0865
Email: sales@opticonusa.com

OPTICON USA

WWW.OPTICONUSA.COM