

CRD-3301

Cradle for OPR-3301
and OPI-3301

Bluetooth®

USB (HID)

RS232



+ Product Specification

Communication

- **RS232:** 600 bps - 57.6 kbps
- **Bluetooth:** Version 1.2, output power class 2, range up to 10m, 1 to 1 connection, slave mode, authentication and encryption
- **USB:** Version 1.1, client, HID, USB-A connector

Power

- **Voltage Requirement:** 6V \pm 5%
- **Battery Charging Time:** Maximum 5 hours with power supply, maximum 10 hours with USB bus power

Durability

- **Temperature:**
Operation: 32 - 104 °F (0 - 40 °C)
Storage: -4 - 140 °F (-20 - 60 °C)
- **Humidity:**
Operation: 25 - 85% (non-condensing)
Storage: 20 - 90% (non-condensing)

Physical

- **Dimensions (WxHxD):** 3.94 x 3.07 x 7.28 in (100 x 78 x 185 mm)
- **Weight (Body):** Ca. 8.5 oz (240 g)
- **Case:** ABS, black or white

Regulatory and Safety

- **Product compliance:** CE, FCC, VCCI, RoHS, EN300 328, EN301 489

Enclosed Items

- USB cable
- RS232 cable
- Power supply 100-240V/0.5A, 50/60 Hz, 6V/2A

Copyright 2014 Opticon. All rights reserved. This information is subject to change without notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp
- **France:** Issy Les Moulineaux
- **Germany:** Dietzenbach
- **Italy:** Castel Maggiore (BO)
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire

- **U.S.A.:** Renton, WA
- **Brazil:** São Paulo
- **Japan:** Warabi City
- **Taiwan:** Taipei
- **P.R.China:** Shanghai

Opticon, Inc.
2220 Lind Ave. SW, Suite 100
Renton, WA 98057
Toll Free: 800.636.0090
Local: 425.651.2120
Fax: 425.454.0865
Email: Sales@OpticonUSA.com
Email: Support@OpticonUSA.com

OPTICON

WWW.OPTICONUSA.COM