

# CRD-32

## Cradle for H-32

USB

Ethernet



### + Product Specifications

#### Communication

- **USB:** Version 2.0, OTG, client and host, micro-USB
- **Ethernet:** RJ45 Ethernet (Ethernet LAN)

#### Power

- **Voltage Requirement:** 6V 2A
- **Charging Method:** Battery in terminal or in spare slot

#### Durability

- **Temperature:**  
Operation: 32 to 104 °F (0 to 40 °C)  
Storage: -4 to 140 °F (-20 to 60 °C)
- **Humidity:**  
Operation: 20% to 80% (non condensing)  
Storage: 20% to 85% (non condensing)

#### Physical

- **Dimensions (WxDxH):** 3.27 x 4.13 x 3.03 in (83 x 105 x 77 mm)
- **Weight Body:** 4.23 oz (120 g)
- **Case:** ABS, black

#### Regulatory and Safety

- **Product Compliance:** CE, FCC, RoHS

#### Sold Separately

- Power supply 6V/2A, Ethernet cable, USB cable

Copyright 2015 Opticon. All rights reserved. This information is subject to change without notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp  
- **France:** Issy Les Moulineaux  
- **Germany:** Dietzenbach  
- **Italy:** Castel Maggiore (BO)  
- **Sweden:** Järfälla  
- **United Kingdom:** Luton, Bedfordshire

- **U.S.A.:** Renton, WA  
- **Brazil:** São Paulo  
- **Japan:** Warabi City  
- **Taiwan:** Taipei  
- **P.R.China:** Shanghai

**Opticon, Inc.**  
2220 Lind Ave. SW, Suite 100  
Renton, WA 98057  
**Toll Free:** 800.636.0090  
**Local:** 425.651.2120  
**Fax:** 425.454.0865  
**Email:** Sales@OpticonUSA.com  
**Email:** Support@OpticonUSA.com

# OPTICON

WWW.OPTICONUSA.COM