

CRD-3301B

Cradle for OPI-3301i and OPC-3301i

SPECIFICATIONS

COMMUNICATION

RS232: 300 bps - 115.2 kbps **BLUETOOTH:** Ver. 3.0 class 2, range up to 10m, 1 to 1 connection, slave mode, authentication and encryption
USB: Ver. 2.0, client, USB-VCP, USB-HID keyboard, USB-a connector

POWER

VOLTAGE REQUIREMENT: 6V ± 5% **BATTERY CHARGING TIME:** Max. 5 hours with power supply, max. 10 hours with USB bus power

DURABILITY

TEMPERATURE IN OPERATION: 0 to 40 °C / 32 to 104 °F **TEMPERATURE IN STORAGE:** -20 to 60 °C / -4 to 140 °F **HUMIDITY IN OPERATION:** 25 - 85% (non-condensing) **HUMIDITY IN STORAGE:** 20 - 90% (non-condensing)

PHYSICAL

DIMENSIONS (W X H X D): 100 x 78 x 185 mm / 3.94 x 3.07 x 7.28 in **WEIGHT BODY:** Ca. 240 g / 8.5 oz **CASE:** ABS, Black or White

REGULATORY & SAFETY

PRODUCT COMPLIANCE: CE, FCC, VCCI, RoHS, EN300 328, EN301 489

ENCLOSED ITEMS

POWER SUPPLY: 100-240V/0.5A, 50/60 Hz, 6V/2A
USB CABLE, RS232 CABLE

