

CRD15E4

Cradle for H15

+ Models

CRD15 Single cradle, serial communication, charging

CRD15E4 Multi-cradle, 4 slots, ethernet communication, charging

+ Specifications

Communication

- Ethernet: RJ45 Ethernet (LAN, UP-Link), 10/100 Base-T

Power

- Voltage requirement: 12V
- Battery charging time: Automatically determined

Durability

- Temperature in operation: 0 to 40 °C / 32 to 104 °F
- Temperature in storage: -20 to 60 °C / -4 to 140 °F

Physical

- Dimensions (w x h x d):
350 x 90 x 115 mm / 13.78 x 3.54 x 4.53 in
- Weight body: Ca. 520 g / 1 lb 2.3 oz
- Case: ABS, Black

Regulatory

- Product compliance: CE, RoHS

Enclosed items

- Power supply 100-240V/1.7A, 50/60 Hz, 12V/5A



Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp
- **France:** Issy Les Moulineaux
- **Germany:** Dietzenbach
- **Italy:** Castel Maggiore (BO)
- **Spain:** Valencia
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Renton, WA
- **Japan:** Warabi City

- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** Kariang
- **Brazil:** São Paulo

Opticon Sensors Europe B.V
European headquarters
Opaallaan 35
2132 XV Hoofddorp
The Netherlands
phone: +31 (0)23-5692700
fax: +31 (0)23-5638266
email: sales@opticon.com
internet: www.opticon.com